



	PLRF25C	VECTOR IV	VECTOR 21	VECTOR 21 Aero	VECTOR 23
観測					
観測	単眼	双眼	双眼	双眼	双眼
倍率	6x	7x	7x	7x	7x
視野角	6° / 106mil	6.75° / 120mil	6.75° / 120mil	6.75° / 120mil	6.75° / 120mil
計測					
距離計測範囲	5m ~ 6000m	5m ~ 6000m	5m ~ 12000m	5m ~ 12000m	25m ~ 25000m
距離計測精度	±2m (50m ~ 1500m) ±5m (<50m / >1500m)	±2m (50m ~ 2000m) ±3m (<50m / >2000m)	±5m	±5m	±5m (500m ~ 12000m)
方位角計測範囲	360°	360°	360°	360°	360°
方位角精度	±0.6° / ±10mil	±0.6° / ±10mil	±0.6° / ±10mil	±0.6° / ±10mil	±0.6° / ±10mil
傾斜角計測範囲	-45° ~ +45°	-45° ~ +45°	-45° ~ +45°	-30° ~ +90°	-45° ~ +45°
傾斜角精度	±0.2° / ±3mil	±0.2° / ±3mil	±0.2° / ±3mil	±0.2° / ±3mil (傾斜角<45°)	±0.2° / ±3mil
物理特性					
重量	500g	< 1.7kg	< 1.7kg	< 1.7kg	< 1.8kg
寸法	131 x 88 x 55mm	205 x 178 x 82mm	205 x 178 x 82mm	205 x 178 x 82mm	205 x 178 x 82mm



	MOSKITO	VECTOR IV Nite	VECTOR 21 Nite
観測			
屋間			
観測	単眼	双眼	双眼
倍率	5x	7x	7x
視野角	6° / 107mil	6.75° / 120mil	6.75° / 120mil
夜間			
観測	単眼	単眼	単眼
倍率	3x	4.5x	4.5x
視野角	10.5° / 187mil	7° / 125mil	7° / 125mil
計測			
距離計測範囲	5m ~ 10000m	5m ~ 6000m	5m ~ 12000m
距離計測精度	±5m	±2m (50m ~ 2000m) ±3m (<50m / >2000m)	±5m
方位角計測範囲	360°	360°	360°
方位角精度	±0.6° / ±10mil	±0.6° / ±10mil	±0.6° / ±10mil
傾斜角計測範囲	-45° ~ +45°	-45° ~ +45°	-45° ~ +45°
傾斜角精度	±0.2° / ±3mil	±0.2° / ±3mil	±0.2° / ±3mil
物理特性			
重量	< 1.2kg	< 2.0kg	< 2.0kg
寸法	130 x 185 x 80mm	205 x 178 x 82mm	205 x 178 x 82mm

＜販売代理店＞

 **極東貿易株式会社**

※ 製品仕様は予告なく変更する場合があります。